

SUMOSPACE+

INTERNAL POWER SUPPLY

No external ballast required.

Entirely passive cooled silent operation. No moving parts.

Same size with increased output


New version of the screwless SUMO SNAP™ Quick Release mount for 16mm Spigot built in



Technical Specifications

- Internal Power Supply
- Increased Powerful Output up to 16.000 Lux [1486 fc] at 3 m [10 ft]; 20° Lens
- · Ultra High Color Rendition TLCI 99, CRI 95
- 0-100% Dimming Range
- . DMX/RDM, Ethernet/Wifi
- 0-100% Dimming Range
- · Flicker Free at all Frame Rates
- 500 W max Power Consumption
- Passive Cooled, No Fans or Moving Parts
- DMX/RDM, Ethernet/WiFi and Wireless Interfaces
- Fixture Weight 6 Kg [13 lbs]
- Bi-Color, Smooth and Accurate Color Adjustment 2.800-6.500 K
- Interchangeable Lens slots for 20°, 30° and 60° Beam Angles
- 120° Fixture Beam Angle
- A variety of Light Shaping tools and mounting options are available.
- SUMO SNAP™ Quick Release mount for 16mm Spigot built in.

Color rendition



TUNGSTEN TLCI 99, CRI 95

DAYLIGHT TLCI 99, CRI 95



Light shaping Tools



SUMODOME Pancake Lantern



Target



Reflector



Reflector, Diffusion Skirt and Target



Reflector, Diffusion Skirt, Black Skirt Covers and Target

Optics

20°, 30° and 60° Interchangeable Lenses

